



55-65 Castleham Road, St Leonards on Sea

East Sussex, TN38 9NU

Customer Services: +44 (0) 1424 856600


T: +44 (0) 1424 856655 F: +44 (0) 1424 856611

E: sales@marshall-tufflex.com

www.marshall-tufflex.com

## **Dry Lining Box 2 Gang Deep Product Data Sheet**

Product Range	MDLB30
Description	Dry Lining Box 2 Gang Deep
Key Features	Wide securing flange.  To suit board thickness from 9mm to 26mm  Swivel snap out clamps  Multiple Entry points  Available with intumescent fire barrier pads
Dimensions	83mm x 143mm over flange 46mm deep To suit hole size 75mm x 135mm
Material(s)	PVCu with Brass Inserts
Compliance / Standards(s)	CE & UKCA Marked Low Voltage Directive 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 BS 7671:2018 BS 5733:2010+A1:2014 BS 476-22:1987 when fitted with intumescent fire barrier pads
Packaging	Recyclable



We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our PVC-U products are manufactured from an average of 80% recycled plastic, with some extruded products produced from 100% recycled material.



Dry Lining Boxes are manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.

To find out more about the percentage of recycled material used in this product, please visit marshall-tufflex.com

DOC00689 Issue 3











Page 1 of 1